

KP6Q - LUXOR SLIM



Date	_____
Project	_____
Location	_____

Commercial Code	KP6Q
Temperature range	+2/ +10°C
Technical features	<p>Display compartment in tempered glass throughout Lower structure in special anti-fingerprintsteel One refrigerated room Cooling unit at evaporation temperature -10 °C and condensation temperature 53,5°C rated at 596 W Climate Class 4, room +30°C and 55% R.H. Ventilated refrigeration obtained through the evaporator being positioned in the lower part of the structure Relative humidity: 70% Automatic defrosting by air, every 6 hours, automatic evaporation of condense drain Ventilated system on the back with the air circulation not directed straight at food Refrigerant fluid: R404A Control board with electronic p.c.b. HACCP alarms (high/low temperature, probes failure, open door and black out)</p>
Functional features	<p>Display shelves in tempered glass. possibility of loading up to 12 kg per shelf. On request available the accessoire KSR25KGP: front bearing kit for shelves, to load up to 25 kg Easily removable magnetic gasket Glass door with “invisible” full-height handle Gross internal volume: 324 litri LED lighting Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company Standard accessories: nr 5 display shelves in tempered glass with the back upright on AISI 304 stainless steel rack Integrated wheels, hidden by the structure. (nr 4)</p>
External size	60x64.5x184cm
Gross/Net weight	171/191kg
Electrical power	0.5 kW Standard connection: V-Hz 230V 1N-/60Hz

